




Appropriate Elastic Models for Interpreting Subduction Zone GPS Data



Ravi Kanda and Mark Simons

I. Motivation

Why Study Subduction Zones?

Plate Collision Zones are locations of :

Primary source of buoyancy driving plate tectonics

Largest fraction of seismicity on Earth (~ 95%)

Largest magnitude earthquakes

Large concentrations of population/infrastructure

Modeling the state of stress and coupling: 10^{-3} - 10^4 yrs

Long Term Goal - Dynamic Modeling:

Continuity, Momentum and Energy balance,

Constitutive Relations (Temperature, Mineralogy), and

Boundary & Initial Conditions

Intermediate Goal - Kinematic Modeling:

Fit Surface Geodetic and Geologic Observations by imposing internal velocities on dislocations in an elastic half-space.


Goals


We want to develop an understanding of why Back-slip model works in modeling subduction zone deformation, in spite of the fact that is it counter-intuitive and is a purely mathematical construct. This is done by developing a more realistic "slab" model that takes the thickness of the subducting slab into account. The backslip model is then explained as a limiting case of the "slab" model, as slab thickness tends to zero, thus giving the backslip model a more intuitive basis.

We also want to determine regions in the world where the backslip model does not work, and see under what conditions the "slab" model explains observed surface deformations better.

Finally, we compare the backslip and slab models to see if the currently available GPS data lets us discriminate between these two models. For this purpose, we use processed (1 year) GPS velocities from GSI, Japan.

The ultimate goal of this endeavor is to be able to relate short-term deformation and its lateral variability to the long-term relationship between seismicity and trench-parallel gravity and topographic anomalies (Song & Simons, 2003).





Conclusions

 $\theta = 15^{\circ}, D = 35 \text{ km}$

 $\theta = 15^{\circ}, D = 52 \text{ km}$

 $\theta = 15^{\circ}, D = 25 \text{ km}$

 $\theta = 8.5^{\circ}, D = 26 \text{ km}$

NorthWest

Kii Peninsula

From Panel II at left, the backslip and slab models differ significantly in their predicted surface deformations just above the locked zone, IFF the slab thickness is larger than locking depth. This is true even for noisy data, or when there is an updip aseismic section.

South East

Horizontal displacements, U., w.r.t. Stn# 925: 385 km from Trench.

-1 0 100 200 300 400 500 60 Distance from Trench. (km)

Both the backslip and slab models fit the GPS horizontal velocity data well. In order to resolve between these two models, we need better vertical GPS velocities (processing in progress). From fitting the horizontal GPS data, however, we possibly see the change in slope associated with the locking depth, in SW Japan (due to shallower dip). In the future, we would like to use leveling or tide-gauge data to complement GPS vertical velocities.